Firewall/VPN - TrustGate200R

# 19" 1U Rack Firewall/VPN for head office / branch office

The TrustGate200R has been designed fully for the large corporate network. With the powerful stateful inspection firewall, the corporate network is well protected against malicious attacks. The firewall offers extensive configuration possibilities, effectively controlling all traffic from both inside and outside.

Equipped with the latest encryption technologies – AES – the TrustGate200R enables up to 600 IPSec tunnels. The implemented CA server allows you not only to save time but also considerable cost, as no 3<sup>rd</sup> party Certificate Authority is needed.

Via EasyTunnels<sup>™</sup> IPSec VPN tunnels can be created and maintained easily and efficiently. The TrustGate200R builds on a flexible platform which can easily be upgraded in the future.

The TrustGate5 has a browser-based interface for ease-of-use. The TrustGate5 is also supported by GateManager for easy, centralized configuration, backup and monitoring. Management with GateManager is very secure, with all communications encrypted.



2 different models

intermate trustgate200R Series

- Stateful inspection firewall with intrusion detection
- 600 IPSec VPN tunnels and 50,000 concurrent connections
- AES encryption in VPN tunnel with 50 Mbps througput
- X.509 digital certificates
- QoS (Traffic Shaping)
- Integrated CA-server
- Centralized management via GateManager™
- Centralized management via GateManager™
- Easy and secure configuration of VPN tunnels via EasyTunnel<sup>™</sup>

# inter mate

# **Technical Specifications**



## Hardware

- 733 MHz Processor
- Power: 90-264VAC, 47-63Hz Autoswitching
- Approvals: UL 1950, CE + EMC (VPN)
- Dimensions, unpacked: 483x45x277mm, 3,63 kg
- Dimensions, packaging incl.: 520x330x110mm, 4,4 kg
- Chassis: 1U Rack 19"
- 2 -year Warranty

#### Firewall

- 100 Mbps Firewall performance
- Stateful Inspection
- Web proxy with anonymization of HTTP request
- URL filtering
- MAC address restriction

# VPN

- AES with fallback to 3-DES or DES
- X.509v3 digital certificate
- SHA-1 and MD5 Authentication
- Self-signed or CA-signed certificate
- Pre-shared key
- Compression
- EasyTunnel ™
- NAT-T / UDP- encapsulation of ESP packets
- QoS (Traffic Shaping)
- Dead Peer detection
- Default VPN Gateway (VPN Router)

#### Management

- TrustGate Launcher for initial contact
- Browser-based configuration and management
- "Drag-and-Drop" firewall and NAT-rules
- Export/import configuration (XML)
- Remote Ping/Trace
- Firmware upgrade via web-interface
- Remote administration, SSL connection
- Network Time Protocol (NTP)
- Extensive status tools
- Logs with search and filtering; e-mail forwarding of logs
- Extensive on-line help and support web site
- Configurable and built-in features to support
  - third-part compatibility
- Centralized management via GateManager™

# Routing

- Choice of WAN IP-assignment mode (DHCP client, PPPoE client, manual/static)
- Support for dynamic IP on WAN
- DHCP Server for clients on LAN
- DHCP Static Lease support
- Static or DHCP/PPP assigned DNS
- Resolves DNS names to IP address
- DNS Proxy on LAN
- WINS Server addresses via DHCP
- Resolves service names to port numbers
- Dynamic and Static NAT/NAPT of both source and destination addresses
- Private Master DNS with routing of DNS server access and DNS-based fail-over
- Support for ISDN Routers

### Options

- Firmware Maintenance Service (FMS)
- Upgrade from the standard 1-year Firmware Maintenance Service (FMS) to a total 3 years. Includes access to the firmware with the latest features and functions as well as general service updates.

inter mate

#### The models differ on the following features:

| Feature   | 232R                        | 242R                            |
|---|-----------------------------|---------------------------------|
| Network Interfaces  | 2 x 10/100BaseTX<br>WAN/LAN | 3 x 10/100BaseTX<br>WAN/LAN/DMZ |
| Free Firmware Maintenance Service   | 1 Year                      | 1 Year                          |
| Concurrent connections  | 35,000                      | 50,000                          |
| DMZ ( 3 <sup>rd</sup> 10/100 Base TX interface) with DNS Proxy and<br>DHCP server for clients on DMZ) | No                          | Yes                             |
| Number of Static Routes   | 128                         | 512                             |
| Number of IP Aliases  | 5                           | 50                              |
| Number of NAT rules dynamic/static  | 256                         | 1024                            |
| Number of VPN tunnels   | 100                         | 600                             |
| Encryption performance in tunnels   | 50 Mbps                     | 50 Mbps                         |
| Integrated CA (certification authority)   | Yes                         | Yes                             |
| EasyTunnel™ Server  | Yes                         | Yes                             |